### Propagation – It's Not Always Free Space



Kai, KE4PT, 2015 Oct 27 Gold Coast ARA

## How Far Can a Pair of 2-meter Handie-Talkies Talk?

#### They can...

 burn up to 160 dB attenuation between the handie-talkie antenna connectors



#### A Better Way to Eat up 160 dB


#### Or we can...

 include two –7 dBi "rubber duckie" antennas, leaving 146 dB for the path



So how far will 146 dB take us?


# Unobstructed Path to ISS Uses up 143 dB



Distance to ISS varies from 400 km (249 mi) straight up, to 2,300 km (1430 mi) on the horizon.


Free Space Path attenuation is 143 dB at the horizon ... we have 3 dB to spare!

## The Cross-town Path Includes Diffractions, Shadows, Reflections




Path attenuation is 146 dB at a distance of just 2.7 km!

# Everyone Benefits from the High Repeater Antenna



Path attenuation to a high repeater antenna is 160 –7+6 dB = 159 dB at a distance of 75 km!

#### 2-meter 5 W Handie-Talkie Range



The green and red curves are median values,

there is a large standard deviation,  $\sigma = 6$  to 10 dB, and tends to increase with distance


#### What Causes Path Attenuation?


#### Signals weaken because of

- Spherical Wave Expansion
- Diffraction and Shadowing
- Scattering
- Fading

#### and

Ohmic losses (we will ignore)






### **Understanding Propagation**

- We first, "assemble" the components of propagation one path at a time
- Then, we build up an "exact" Eye-Glazing Formula from the components and paths
- Last, radically simplify the Eye-Glazer because of how Ham FM receivers work

#### We'll omit many explanations and physical details


### Receiving Capture Area



1st component is Free Space Propagation, or, inverse square law, 20 dB for every decade of distance

J. Hallas, W1ZR, "Antenna Gain, Part III: How Much Signal Gets Received?" QST, Jan 2016, [scheduled].

### Propagation with Many Scatterers




- (a) Attenuation by expanding spherical wave
- (b) Energy bleeding into 4th dimension: time!

### Build Up the Eye-Glazing Equation


- (1) Free Space spherical expansion component
- (2) Scaling factor component
- (3) Each impulse "echo" component

# Scatterers Create Time-delayed Impulses (copies of the signal)




Free Space attenuation modifies the impulse echoes

# The Number of Scatterers, and Impulses, Increase with Range



More time-delayed impulses are involved as distance from the transmitter increases

### The Eye-Glazing Finale ...



Free Space attenuation modifies time delayed impulse echoes, a <u>rake diversity</u> receiver can capture this energy


K. Siwiak, H. L. Bertoni, and S. Yano, "Relation between multipath and wave propagation attenuation", Electronic Letters, 9 Jan 2003, Vol. 39 Num 1, pp. 142-143.

## Now, It All Depends on Your Antenna and Receiver!

- So far, we've described the raw energy components at the receiving location
- What happens next depends on the
  - Antenna (we'll assume a typical linearly polarized ham antenna)
  - The type of receiver (we'll assume a typical Ham FM receiver)

Yes! the receiving system impacts the system propagation law!

# Ham FM Receivers Lock Onto Just ONE Impulse



The rest of the impulse energy shifts into the 4<sup>th</sup> dimension (time) and contributes to fading!

### The Eye-Glazer **busted!**

$$W(D_{km}) \approx \left[ \frac{1}{\left(42F_{MHz}D_{km}\right)^{2}} \right]$$

$$\times \left(1 - e^{\left[\frac{-t_{0}}{\tau_{d}(D_{km})}\right]}\right)$$

 $\frac{t_0}{\tau_d(D_{km})} = \left(\frac{D_B}{D_{km}}\right)^M$ 

 $W_0(D_{km}) \approx \frac{\left(\frac{D_B}{D_{km}}\right)^M}{\left(42F_{MHz}D_{km}\right)^2}$ 

Receiver locks to <u>only</u> the strongest impulse (*n*=0)

- D<sub>B</sub> is roughly the distance to the first scatterer
- $\emph{M}$  is between 0.5 and 2.5 depending on how delay spread  $\tau_d$  increases

Multipath creates a <u>2+*M* inverse power attenuation</u>, rest of the energy shifts into time and contributes to fading!


K. Siwiak, "Radio Wave Propagation: How Waves Attenuate with Distance", QST, Feb 2016, [scheduled].

#### The Bottom Line


$$W_0(D_{km}) \approx \frac{\left(\frac{D_B}{D_{km}}\right)^M}{\left(42F_{MHz}D_{km}\right)^2}$$

- D<sub>B</sub> is roughly the distance to the first scatterer
- *M* is between 0.5 and 2.5 depending on how delay spread  $\tau_d$  increases

#### ... can be written as decibels of loss:



#### Different Propagation Laws



### Summary

- Radio waves expand spherically
- Additional energy can be lost to
  - Diffraction
  - Reflection
  - Scattering and Cross Polarization
  - The 4<sup>th</sup> dimension
  - Heating up the environment
- The path determines the details



Thanks for your Attention